

FLOOR SANDING SHEETS 205 x 475mm SILICON CARBIDE - PAPER BACKED

P5-FSS





IDEALLY SUITED OCCAS	SIONAL USE
MATERIAL	
EXPANDING FILLER	
FIBRE GLASS	
HARD WOOD	
JOINT COMPOUND	
METAL	
PAINT	
PLASTER	
тіс	
SOFT WOOD	
SURFACE FILLER	
VARNISH	

Also avaliable: **P5-FSDB**





Bag retaining rings AP10519A

> Dust control bags AP10519

DESCRIPTION: Suitable for use on rotary drum sanders, including: Hire Tech HT8 and Clarke EZ8.

MACHINE SUITABILITY: Rotary drum sanders, including: Hire Tech HT8 and Clarke EZ8.

STANDARDS:

• EN13743: European standard that regulates the safety requirements for coated abrasve products. (sanding sheets and discs.)

USER TIPS:

- To reduce the risk of damaging discs, ensure that any purtruding nails are hammered home or removed, and any split or damaged boards and repaired.
 For the best results, start with a coarse grit i.e. P24,
- For the best results, start with a coarse grit i.e. P24, and then a medium grit (P60 or P80), finally using P120 to achieve a clean and smooth finish.
- Ensure that the sheet is fitted tightly to the drum and the clamping bar is fully tightened.

PACKAGING DETAILS:

Full colour corrugated cardboard box.



E sales@premierdiamondproducts.co.uk

PRODUCT DETAILS:

Part No.	Grit	Pack Qty.
AP10511	P24*	25
AP10512	P24	25
AP10514	P24	25
AP10515	P24	25
AP10516	P24	25
AP10517	P24	25
AP109519	N/A	50
AP10519A	N/A	10
*OPEN GRIT		





T +44 (0) 1227 711 555



www.premierdiamondproducts.co.uk

150 14001 2015 CM5 9001 2015

CUTTING EDGE TECHNOLOGY