

P5-PLUNGE

SPEC SHEET



■ IDEALLY SUITED
 ■ OCCASIONAL USE

MATERIAL	
ALUMINIUM	
C12 KILN DRIED TIMBER	
C24 PRESSURE TREATED TIMBER	
CHIPBOARD	
COMPOSITE DECKING	
HARDWOOD	
HARDBOARD	
LAMINATED BOARD	
LAMINATED FLOORING	
MDF	
MILD STEEL	
NAIL EMBEDDED WOOD	
PLASTIC	
PLYWOOD	
ROOFING BATTEN	
STAINLESS STEEL	
SOFTWOODS	
TIMBER DECKING	

DESCRIPTION: Premium wood cutting TCT blades for use on 160 and 165mm plunge saws. Manufactured using high grade carbide teeth for long life and precision hardened steel plates for maximum stability.

FEATURES: Premium quality TCT teeth, ATB +5°

MACHINE SUITABILITY: TCT Plunge saws.

PRODUCT DETAILS:

Part No.	Dimensions
GT11079	160 x 2.2 x 1.6 x 20mm x 24 Teeth
GT11080	160 x 2.2 x 1.6 x 20mm x 48 Teeth

USER TIPS:

- Ensure that the cutting depth of the machine is set correctly for the material being cut
- Do not force the cut. Let the blade and machine do the work
- Always ensure that the blade is suitable for your machine type. Using a blade designed for another machine type could be unsafe.
- Make certain that the blade is suitable for the material being cut
- The higher the tooth count, the cleaner the cut and the lower the tooth count, the faster the cut.

PACKAGING DETAILS:

Polypropylene Plastic PP5 clam shell - fully recyclable.



E sales@premierdiamondproducts.co.uk T +44 (0) 1227 711 555



www.premierdiamondproducts.co.uk



CUTTING EDGE TECHNOLOGY