

ST-SDSP ST2

SPEC SHEET



■ IDEALLY SUITED
 ■ OCCASIONAL USE

MATERIAL	
ASPHALT	
ASPHALT OVER CONCRETE	
CAST CONCRETE	
CEMENT SCREED	
CHALK STONE	
CONCRETE - BEAMS, KERBS, PIPES & SLABS	
CONCRETE BLOCK PAVIOURS	
CONCRETE LINTELS	
CONCRETE PIPES	
COTSWOLD STONE	
ENGINEERING BRICKS	
EXTERIOR RENDER	
FACING BRICKS	
FLINT AGGREGATE CONCRETE	
GREEN CONCRETE	
LIMESTONE	
MORTAR	
REINFORCED CONCRETE	
SANDSTONE - ABRASIVE & GRITSTONE	
YORK STONE	

DESCRIPTION: The 2-cutter ST2 range of drill bits offer good value for money across a wide range of masonry materials.

SIZE RANGE: Diameters 5.5mm, 6mm, 7mm and 8mm available in 160mm overall drill length, and 7mm, 10mm and 12mm available in 210mm overall drill length.

FEATURES:

- High drilling speed
- Powerful dust rejection spiral ensures smooth and fast drilling


MACHINE SUITABILITY: SDS-PLUS

USER TIPS:

- Always use the side handle provided with the machine
- Do not use excessive pressure, just enough to keep the bit in constant contact with the surface you are drilling
- Remember to clear the excess debris from the hole whilst drilling. Do this by periodically moving the bit in and out of the hole. This will reduce the risk of the bit binding in the hole
- Once you have drilled to the desired depth, allow the bit to spin whilst withdrawing from the hole to remove as much of the debris as possible.

PACKAGING DETAILS:

Full colour corrugated cardboard box.



E sales@premierdiamondproducts.co.uk T +44 (0) 1227 711 555