



# SOFTWOOD & PLYWOOD JIGSAW BLADE (T-SHANK)

## ST-JSB T101D



- IDEALLY SUITED
- UNSUITABLE
- OCCASIONAL USE

MATERIALS	
ALUMINIUM	
CHIPBOARD	<input checked="" type="checkbox"/>
CONSTRUCTION TIMBER	<input checked="" type="checkbox"/>
FIBRE BOARD (MDF)	<input checked="" type="checkbox"/>
FIBRE CEMENT BOARD	
GLASS FIBRE REINFORCED PLASTIC (GRP)	
LAMINATE	
NAIL EMBEDDED WOOD	
NON FERROUS METALS (COPPER, ZINC, LEAD)	
PLASTER BOARD	
PLASTIC (PVC)	
PLYWOOD	<input checked="" type="checkbox"/>
STEEL SECTION (PIPE, ANGLE, BOX)	
STEEL SHEET	
WOOD - CLEAN HARDWOOD	
WOOD - CLEAN SOFTWOOD	<input checked="" type="checkbox"/>

### DESCRIPTION:

Suitable for cutting softwood, plywood, chipboard and Fibre Board (MDF). The ST-JSB T101D has ground, tapered teeth for a fine, clean, and straight cut, in material thicknesses of 10mm to 45mm.

### FEATURES:

- Made from High Carbon Steel (HCS)
- Precision-ground teeth, with a Taper-ground body

### MACHINE SUITABILITY:

All T-shank Jigaws, inc Makita, Bosch, Dewalt, Festool, Erbauer & Hikoki

### USER TIPS:

- Always wear the appropriate PPE
- Ensure you select the correct blade for your task
- Disconnect the power/ remove the battery prior to fitting or removing a blade
- If you have a variable speed Jigsaw, select faster speeds for soft materials, and slower speeds for harder materials such as Steel
- If your Jigsaw has an oscillating option, this will increase the speed of cut, but reduce the finish quality
- Always ensure that the foot plate is flat to the surface before cutting
- When starting a cut, make gentle contact with the material, forcing the cut will cause the blade to jump and damage the teeth
- Once you have completed your cut, wait for the blade to stop, before removing from the material
- Blades that cut on the up stroke will leave a feathered edge to the surface of the material, but are smoother and easier to use. Select a reverse cut/ down cut blade to ensure a clean finish to the cutting surface.

### PRODUCT DETAILS:

PART NO.	SIMILAR TO	PACK QTY.	BLADE MATERIALS & THICKNESS	OVERALL LENGTH	TOOTH SPACING & TPI	APPLICATIONS
GT42005	T101D	5	HCS/ 1.5mm	100mm/75mm	4mm/ 6TPI	Softwood & Timber Sheeting 10mm to 45mm Thick

### FINISH:

Clean

### PACKAGING DETAILS:

Full colour cardboard sleeve.



✉ sales@premierdiamondproducts.co.uk ☎ +44 (0) 1227 711 555

Another quality product from Premier Diamond Products ISO Certified Company



www.premierdiamondproducts.co.uk