



# SOFTWOOD & TIMBER SHEET - FAST CUTTING JIGSAW BLADE (T-SHANK)

## ST-JSB T144D



<input checked="" type="checkbox"/>	IDEALLY SUITED	<input type="checkbox"/>	UNSUITABLE
<input checked="" type="checkbox"/>	OCCASIONAL USE		

### MATERIALS

ALUMINIUM	
CHIPBOARD	
CONSTRUCTION TIMBER	
FIBRE BOARD (MDF)	
FIBRE CEMENT BOARD	
GLASS FIBRE REINFORCED PLASTIC (GRP)	
LAMINATE	
NAIL EMBEDDED WOOD	
NON FERROUS METALS (COPPER, ZINC, LEAD)	
PLASTER BOARD	
PLASTIC (PVC)	
PLYWOOD	
STEEL SECTION (PIPE, ANGLE, BOX)	
STEEL SHEET	
WOOD - CLEAN HARDWOOD	
WOOD - CLEAN SOFTWOOD	

### DESCRIPTION:

Fast cutting in wood, the ST-JSB T144D's ground and side set teeth, and coarse cutting 6 TPI, deliver rapid cuts in softwood, plywood, chipboard and Fibre Board (MDF), when a clean finish is not paramount.

### FEATURES:

- Made from High Carbon Steel (HCS)
- Sharp Ground, Side Set Teeth
- Fast Cutting

### MACHINE SUITABILITY:

All T-shank Jigaws, inc Makita, Bosch, Dewalt, Festool, Erbauer & Hikoki

### USER TIPS:

- Always wear the appropriate PPE
- Ensure you select the correct blade for your task
- Disconnect the power/ remove the battery prior to fitting or removing a blade
- If you have a variable speed Jigsaw, select faster speeds for soft materials, and slower speeds for harder materials such as Steel
- If your Jigsaw has an oscillating option, this will increase the speed of cut, but reduce the finish quality
- Always ensure that the foot plate is flat to the surface before cutting
- When starting a cut, make gentle contact with the material, forcing the cut will cause the blade to jump and damage the teeth
- Once you have completed your cut, wait for the blade to stop, before removing from the material
- Blades that cut on the up stroke will leave a feathered edge to the surface of the material, but are smoother and easier to use. Select a reverse cut/ down cut blade to ensure a clean finish to the cutting surface.

### PRODUCT DETAILS:

PART NO.	SIMILAR TO	PACK QTY.	BLADE MATERIALS & THICKNESS	OVERALL LENGTH	TOOTH SPACING & TPI	APPLICATIONS
GT42011	T144D	5	HCS/ 1.2mm	100mm/75mm	4mm/ 6TPI	Softwood & Timber Sheeting 5mm to 50mm Thick

### FINISH:

Rough

### PACKAGING DETAILS:

Full colour cardboard sleeve.



✉ sales@premierdiamondproducts.co.uk ☎ +44 (0) 1227 711 555

Another quality product from  
Premier Diamond Products  
ISO Certified Company

**PREMIER**  
DIAMOND PRODUCTS



www.premierdiamondproducts.co.uk