

# ST-MTB-SBP/SP



IDEALLY SUITED  
 OCCASIONAL USE

UNSUITABLE

## MATERIALS

ADHESIVE REMOVAL	<input checked="" type="checkbox"/>
ALUMINIUM	<input checked="" type="checkbox"/>
SOFT TILES (NOT PORCELAIN)	<input checked="" type="checkbox"/>
CHIPBOARD	<input checked="" type="checkbox"/>
FIBRE BOARD (MDF)	<input checked="" type="checkbox"/>
FIBRE CEMENT BOARD	<input checked="" type="checkbox"/>
GLASS FIBRE REINFORCED PLASTIC (GRP)	<input checked="" type="checkbox"/>
LAMINATE	<input checked="" type="checkbox"/>
SOFT MASONRY & MORTAR	<input checked="" type="checkbox"/>
MELAMINE	<input checked="" type="checkbox"/>
NAIL EMBEDDED WOOD	<input checked="" type="checkbox"/>
NON FERROUS METALS (COPPER, ZINC, LEAD)	<input checked="" type="checkbox"/>
NUTS & BOLTS	<input checked="" type="checkbox"/>
ORIENTED STRAND BOARD (OSB)	<input checked="" type="checkbox"/>
PLASTER BOARD	<input checked="" type="checkbox"/>
PLASTICS (PVC, PE, PS, PP, PC & COMPOSITES)	<input checked="" type="checkbox"/>
PLYWOOD	<input checked="" type="checkbox"/>
MILD STEEL <2MM	<input checked="" type="checkbox"/>
RESIN & HARD ADHESIVES	<input checked="" type="checkbox"/>
SCREWS & NAILS (ALL TYPES)	<input checked="" type="checkbox"/>
SOFT SCREWS & NAILS (NOT STAINLESS STEEL)	<input checked="" type="checkbox"/>
SURFACE SCRAPING (I.E. SILICON, CAULK, ETC.)	<input checked="" type="checkbox"/>
TILE GROUT & ADHESIVE REMOVAL	<input checked="" type="checkbox"/>
WOOD - CLEAN HARDWOOD	<input checked="" type="checkbox"/>
WOOD - CLEAN SOFTWOOD	<input checked="" type="checkbox"/>

## DESCRIPTION:

The ST-MTB Sanding Range consist of an 80mm delta backing pad and 3 different grits of aluminium oxide sanding sheets. Featuring Hook & Loop fitting, making it quick and easy to position and remove the sanding sheets.

## FEATURES:

Hook & Loop fitting, for speedy sanding sheet changes

## MACHINE SUITABILITY:

Universal Fitting – Fits most brands of machine

## USER TIPS:

- Always wear the appropriate PPE
- Make sure that the attachment is the correct fitting for your machine
- Ensure that the sanding sheet is positioned correctly on the back pad
- Avoid using excess pressure when sanding. Excess pressure will not improve the sanding performance and may result in damage to the back pad
- If the effectiveness of the sanding sheet reduces, then simply replace the sanding sheet and continue

## PRODUCT DETAILS:

PART NO.	WIDTH	PRODUCT TYPE	PACK QTY	BLADE MATERIALS	MATERIAL APPLICATION
GT42152	80mm Delta	Back Pad	1	Eva - Hook & Loop Fitting	Sanding
GT42153	80mm Delta	Sand Paper	10	60 Grit Aluminium Oxide	Sanding
GT42154	80mm Delta	Sand Paper	10	80 Grit Aluminium Oxide	Sanding
GT42155	80mm Delta	Sand Paper	10	120 Grit Aluminium Oxide	Sanding

## PACKAGING DETAILS:

Full colour corrugated cardboard box.



Widely Recycled

View Online

[sales@premierdiamondproducts.co.uk](mailto:sales@premierdiamondproducts.co.uk) +44 (0) 1227 711 555