



RECIPROCATING SAW BLADES

WOOD & METAL CUTTING

ST-RB S1222VF

SPEC SHEET



DESCRIPTION:

Optimised for use in the repair of and cutting up of wooden pallets. The blade's variable TPI provides a smooth cut with minimal vibration. Its additional length and flexible nature means that the blade can be used to cut flush through the pallet's joints to a depth of 250mm. (Maximum cutting depth 250mm)

PACKAGING DETAILS:

Full colour cardboard box.



CARDBOARD

Widely Recycled

<input checked="" type="checkbox"/>	IDEALLY SUITED	<input type="checkbox"/>	UNSUITABLE
<input checked="" type="checkbox"/>	OCCASIONAL USE		

MATERIALS

ALUMINIUM	
CAST IRON	
CHIPBOARD	
CONSTRUCTION TIMBER	
EPOXY	
GLASS FIBRE ENFORCED PLASTIC (GRP)	
LIGHTWEIGHT BUILDING BLOCKS	
MEDIUM DENSITY FIBRE BOARD	
NAIL EMBEDDED WOOD	
NON FERROUS METALS (COPPER, ZINC, LEAD)	
PLASTIC	
PLYWOOD	
SCAFFOLD BOARD - CLEAN	
SCAFFOLD BOARD - METAL EMBEDDED (INC. END STRAPS)	
SCAFFOLD TUBE - GALVANISED (ALL THICKNESSES)	
STEEL SECTION (PIPE, ANGLE, BOX)	
TREE PRUNING / GREEN WOOD	
WOOD - CLEAN HARDWOOD	
WOOD - CLEAN SOFTWOOD	

PRODUCT DETAILS:

PART NO.	SPEC	SIMILAR TO	APPLICATION	OVERALL LENGTH & TPI	BLADE MATERIALS & THICKNESS
GT42036	ST-RB S1222VF	S1222VF	Flexible Wood & Metal Cutting	300mm/10-14TPI	BIM/0.96mm

✉ sales@premierdiamondproducts.co.uk ☎ +44 (0) 1227 711 555

Another quality product from
Premier Diamond Products
ISO Certified Company

PREMIER
DIAMOND PRODUCTS



www.premierdiamondproducts.co.uk