

RECIPROCATING SAW BLADES

UNSUITABLE

IDEALLY SUITED

MATERIALS ALUMINIUM CAST IRON CHIPBOARD CONSTRUCTION TIMBER

PLASTIC PLYWOOD

SCAFFOLD BOARD - CLEAN

STEEL SECTION (PIPE, ANGLE, BOX) TREE PRUNING / GREEN WOOD WOOD - CLEAN HARDWOOD WOOD - CLEAN SOFTWOOD

OCCASIONAL USE

GLASS FIBRE ENFORCED PLASTIC (GRP) LIGHTWEIGHT BUILDING BLOCKS MEDIUM DENSITY FIBRE BOARD NAIL EMBEDDED WOOD

NON FERROUS METALS (COPPER, ZINC, LEAD)

SCAFFOLD BOARD - METAL EMBEDDED (INC. END STRAPS) SCAFFOLD TUBE - GALVANISED (ALL THICKNESSES)







PRODUCT DETAILS:

PART NO. SIMILAR TO **APPLICATION OVERALL LENGTH BLADE MATERIALS** & THICKNESS & TPI ST-RB S1122AF Flexible Metal Cutting BIM/0.96mm GT42030 S1122AF 228mm/24TPI

DESCRIPTION:

The fine tooth pitch and high TPI of this blade gives a reliable and clean cut through thin gauge steel and non-ferrous metals up to 2mm thick. The flexibility of the blade makes it ideal for flush cutting in materials such as sheet metals, pipes and profiles. (Maximum working depth 175mm)

PACKAGING DETAILS:

Full colour cardboard box.









