



RECIPROCATING SAW BLADES METAL CUTTING

ST-RB S1122EF

SPEC SHEET



- IDEALLY SUITED
- OCCASIONAL USE
- UNSUITABLE

MATERIALS	
ALUMINIUM	
CAST IRON	
CHIPBOARD	
CONSTRUCTION TIMBER	
EPOXY	
GLASS FIBRE ENFORCED PLASTIC (GRP)	
LIGHTWEIGHT BUILDING BLOCKS	
MEDIUM DENSITY FIBRE BOARD	
NAIL EMBEDDED WOOD	
NON FERROUS METALS (COPPER, ZINC, LEAD)	
PLASTIC	
PLYWOOD	
SCAFFOLD BOARD - CLEAN	
SCAFFOLD BOARD - METAL EMBEDDED (INC. END STRAPS)	
SCAFFOLD TUBE - GALVANISED (ALL THICKNESSES)	
STEEL SECTION (PIPE, ANGLE, BOX)	
TREE PRUNING / GREEN WOOD	
WOOD - CLEAN HARDWOOD	
WOOD - CLEAN SOFTWOOD	

DESCRIPTION:

Designed to cut through the most common wall thicknesses of steel and non-ferrous metals from 1.5mm to 4mm thick. The blade's flexibility makes it ideal for flush cutting materials such as sheet metals, pipes and profiles. (Maximum working depth 175mm)

PRODUCT DETAILS:

PART NO.	SPEC	SIMILAR TO	APPLICATION	OVERALL LENGTH & TPI	BLADE MATERIALS & THICKNESS
GT42032	ST-RB S1122EF	S1122EF	Flexible Metal Cutting	228mm/18TPI	BIM/0.96mm

PACKAGING DETAILS:

Full colour cardboard box.



✉ sales@premierdiamondproducts.co.uk ☎ +44 (0) 1227 711 555

Another quality product from Premier Diamond Products
ISO Certified Company



www.premierdiamondproducts.co.uk