

RECIPROCATING SAW BLADES METAL CUTTING





PRODUCT DETAILS:

ST-RB S922EF

GT42044

SIMILAR TO

S922EF



DESCRIPTION:

Designed to cut through the most common wall thicknesses of steel and non-ferrous metals, from 1.5mm to 4mm thick. The blade's flexibility makes it ideal for flush cutting on materials such as sheet metals, pipes and profiles. (Maximum working depth 100mm)

PACKAGING DETAILS:

Full colour cardboard box.



IDEALLY SUITED	UNSUITABLE
OCCASIONAL LISE	

	MATERIALS	
	ALUMINIUM	
	CAST IRON	
	CHIPBOARD	
	CONSTRUCTION TIMBER	
	EPOXY	
	GLASS FIBRE ENFORCED PLASTIC (GRP)	
	LIGHTWEIGHT BUILDING BLOCKS	
	MEDIUM DENSITY FIBRE BOARD	
	NAIL EMBEDDED WOOD	
	NON FERROUS METALS (COPPER, ZINC, LEAD)	
	PLASTIC	
	PLYWOOD	
	SCAFFOLD BOARD - CLEAN	
	SCAFFOLD BOARD - METAL EMBEDDED (INC. END STRAPS)	
	SCAFFOLD TUBE - GALVANISED (ALL THICKNESSES)	
	STEEL SECTION (PIPE, ANGLE, BOX)	
	TREE PRUNING / GREEN WOOD	
	WOOD - CLEAN HARDWOOD	
	WOOD - CLEAN SOFTWOOD	
APPLICATION OVERALL LENGTH BLADE MATERIALS		

& TPI

Flexible Metal Cutting

150mm/18TPI

& THICKNESS

BIM/0.96mm

⊠sales@premierdiamondproducts.co.uk 🗘 +44 (0) 1227 711 555







