

<u>ST-SDSP ST4</u>

SPEC SHEET

DESCRIPTION:

The ST-4 4-cutter drill bits use an automated copper soldering process to adhere the high quality tungsten carbide tips, giving them added strength. This allows them to perform on tough applications such as concrete, bricks, blocks and natural stone.

SIZE RANGE:

Over 45 diameters from 5mm to 32mm, in lengths from 110mm to 1000mm

FEATURES:

- 4-cutter Design for longer life
- Powerful dust rejection, due to a specially engineered spiral design
- Ideal for resin anchors

MACHINE SUITABILITY:

SDS-PLUS

PACKAGING DETAILS:

Polypropylene (PP5) plastic hanging tab.





Sales@premierdiamondproducts.co.uk 🕻 +44 (0) 1227 711 555

PREMIER

DIAMOND PRODUCTS

DOD

PRODUCT DETAILS:

PART NO.	DIAMETER	OVERALL LENGTH	WORKING LENGTH	
GT40205	5mm	110mm	50mm	
GT40206	5mm	160mm	100mm	
GT40208	5.5mm	110mm	50mm	
GT40209	5.5mm	160mm	100mm	
GT40211	6mm	110mm	50mm	
GT40212	6mm	160mm	100mm	
GT40213	6mm	210mm	150mm	
GT40214	6mm	260mm	200mm	
GT40216	6.5mm	160mm	100mm	
GT40217	6.5mm	210mm	150mm	
GT40218	6.5mm	260mm	200mm	
GT40220	7mm	160mm	100mm	
GT40221	7mm	210mm	150mm	
GT40222	7mm	260mm	200mm	
GT40224	8mm	160mm	100mm	
GT40225	8mm	210mm	150mm	
GT40226	8mm	260mm	200mm	
GT40228	10mm	160mm	100mm	
GT40229	10mm	210mm	150mm	
GT40230	10mm	260mm	200mm	
GT40231	10mm	460mm	400mm	
GT40233	10mm	1000mm	940mm	
GT40234	12mm	160mm	100mm	
GT40235	12mm	210mm	150mm	
GT40236	12mm	260mm	200mm	
GT40238	12mm	460mm	400mm	
+44 (0) 1227 711 555				

ISO 9001

ISO 14001

SDS PLUS DRILL BITS 4-CUTTER MASONRY DRILL

IDEALLY SUITED

UNSUITABLE

OCCASIONAL USE

MATENIALO			
ASPHALT			
ASPHALT OVER CONCRETE			
CAST CONRETE			
CEMENT SCREED			
CHALK STONE			
CONCRETE - BEAMS, KERBS, PIPES & SLABS			
CONCRETE BLOCK PAVIOURS			
CONCRETE LINTELS			
CONCRETE PIPES			
COTSWOLD STONE			
ENGINEERING BRICJKS			
EXTERIOR RENDER			
FACING BRICKS			
FLINT AGGREGATE CONCRETE			
GREEN CONCRETE			
LIMESTONE			
MORTAR			
REINFORCED CONCRETE			
SANDSTONE - ABBRASIVE & GRITSTONE			
YORK STONE			

PART NO.	DIAMETER	OVERALL LENGTH	WORKING LENGTH
GT40240	12mm	1000mm	940mm
GT40241	14mm	160mm	100mm
GT40242	14mm	210mm	150mm
GT40243	14mm	260mm	200mm
GT40244	14mm	310mm	250mm
GT40245	14mm	460mm	400mm
GT40246	15mm	260mm	200mm
GT40247	16mm	210mm	150mm
GT40248	16mm	310mm	250mm
GT40249	16mm	460mm	400mm
GT40251	16mm	1000mm	940mm
GT40252	18mm	210mm	150mm
GT40253	18mm	310mm	250mm
GT40254	18mm	460mm	400mm
GT40257	20mm	210mm	150mm
GT40258	20mm	310mm	250mm
GT40259	20mm	460mm	400mm
GT40260	20mm	1000mm	940mm
GT40262	22mm	260mm	200mm
GT40263	22mm	460mm	400mm
GT40268	24mm	460mm	400mm
GT40273	25mm	460mm	400mm
GT40275	25mm	1000mm	940mm
GT40280	28mm	350mm	290mm
GT40281	28mm	460mm	400mm
GT40285	30mm	460mm	400mm
GT40289	32mm	460mm	400mm

tion ISO Certification

Another quality product from Premier Diamond Products